


## Part Number A4138, Tapered Roller Bearings - Single Cups - Imperial

This is the most basic and most widely used type of tapered roller bearing. It consists of two main separable parts: the cone (inner ring) assembly and the cup (outer ring). It is typically mounted in opposing pairs on a shaft.





## Specifications | Dimensions | Abutment and Fillet Dimensions | Factors

Specifications –			
	Series	A4000	
	Cup Part Number	A4138	
	Design Units	Imperial	
Dimensions –			
	D - Cup Outer Diameter	1.3775 in 34.989 mm	
	C - Cup Width	0.3437 in 8.730 mm	

r - Cup Backface "To Clear" Radius <sup>1</sup>	0.050 in 1.27 mm	
Da - Cup Frontface Backing Diameter	1.28 in 32.51 mm	
Db - Cup Backface Backing Diameter	1.14 in 28.96 mm	
actors		
e - ISO Factor <sup>2</sup>	0.45	
Y - ISO Factor <sup>3</sup>	1.32	

<sup>1</sup> These maximum fillet radii will be cleared by the bearing corners.

Cg - Geometry Factor<sup>4</sup>

 $^2$  These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.

0.0355

 $^{3}$  These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.

<sup>4</sup> Geometry constant for Lubrication Life Adjustment Factor a3I.

